



IP INTEROPERABILITY SOLUTION

Achieve a new level of interoperability and increase communication, safety and productivity by expanding your existing IP network to include your LMR two-way radio users (**RoIP**).

The Ritron **RadioNexus™** network-ready LMR base station transceiver is available in VHF and UHF frequency band models. A built-in RJ-45 connector and Type 3 E&M analog interface allows easy connection to the IP network using a simple router or **VoIP** gateway.

When connected to the IP network via a router or VoIP gateway the Ritron **RadioNexus™** enables compatible LMR radios to communicate across the IP network to **any other networked device** (i.e. PC, laptop, IP phone, cell phone) including two-way radios regardless of make, model, frequency band or signaling format (equivalent hardware/software may be required at opposite end). For even greater talk range and/or increased penetration in and around buildings, the **RadioNexus™** can even be programmed to communicate with a radio repeater.



For maximum compatibility with other LMR radios the Ritron **RadioNexus™** can be programmed to work with virtually any brand of VHF or UHF business band radios. Features include: PC programmability, rugged, all-steel, heavy-duty construction, 2 Watt transmitter, Automatic "ON" feature, CTCSS or DCS signaling, wide or narrow band operation, BNC connector for external antenna, local speaker, local microphone jack, small and compact size (only 1.4"H x 3.8"W x 5.6" L), wall or desk mountable, 110 VAC or 12 VDC operation.

VHF "License-Free" models are available

Markets:

- Local, State, and Federal Government
- Businesses
- Schools, Colleges, Universities
- Retail Operations

For over 27 years, Ritron has been designing and manufacturing a wide range of wireless solutions. They include portable and mobile 2-way radios, base stations, radio extender repeaters, radio callboxes, telemetry systems, voice alarm reporters and OEM transceivers.

Ritron recommends a supported Cisco router model 2651XM, 3725 or 3745 with the following installed options NM-HD-2V, VIC2-2E&M.

For enhanced communication capability with other network devices and LMR radios, Ritron recommends the WAVE (Wide Area Voice Environment) software application from Twisted Pair Solutions. For a whitepaper on LMR integration go to <http://www.twistpair.com/inc/data/Application%20Brief/wave-app-ab-8.5x11.pdf>



505 W. Carmel Drive · Carmel, IN 46032
317-846-1201 · Fax: 317-846-4978
Email: ritron@ritron.com
www.ritron.com

