TC320

Business Analog Portable Radio

Unique for its compact and professional design, as well as its superb sound quality. Its strong casing prevents damage against drops of up to 5ft. This radio enables businesses to enjoy dependable communications at an extremely low cost.

Highlights

- Wide Communication Range
  2W output power has a range of up to 6 miles.
- Durable Casing
  Compact durable design that can with stand a 1.5 meter drop.
- Long Battery Life
  1700mAh high capacity Li-Ion battery lasts approximately 12hrs.
- User Friendly Design
  With its ergonomic design, this slim and compact radio can enhance user comfort, while maintaining a professional and fashionable appearance.
- Double Injection Molding
  The combination of double injection molding and grip technology brings users a comfortable and convenient operation experience.
- Mini-USB Interface
  Chargeable and Programmable through the Mini-USB port, plug directly into an outlet or the optional charger.

Features

- Audio Compandor
- Scrambler compatible w/ TC320 UHF2 & TC518
- VOX Earpiece
- Battery Strength Indicator
- High / Low Power Switchable
- Programmable 25 / 12.5 KHz Channel Spacing
- Monitor
- CTCSS / CDCSS and Squelch Tail Elimination
- Channel Scan
- Auto Battery Save
- Low Battery Alert
- Busy Channel Lockout (BCL)
- Time-out-timer (TOT)
- PC Programmable
- Wired Clone

Applications

Retail | Hotel | Restaurants | Education | Hospital | Business | Property Management

Accessories

Included
- Li-Ion Battery
- Power Supply
- Antenna
- Belt Clip
- Neck Strap

Optional

See website for full list

Earpiece with In-Line MIC, PTT, & VOX
EHS09

Rapid-rate Charger (for Li-Ion Battery)
CH05L01

Programming Cable (USB Port)
PC30

6-Unit Switching Power (Combine w/ CH05L01)
PS4001

Specifications

General	Frequency Range	UHF1: 400 - 470MHz ; UHF2: 450-470MHz
	Channel Capacity	16
	Channel Spacing	25 / 12.5KHz
	PLL Channel Stepping	5 kHz, 6.25 kHz
	Operating Voltage	3.7V (rated)
	RF Power Output	2W
	Battery	1700mAh (Li-Ion)
	Battery Life (5-5-90 Duty Cycle)	Approx. 10hrs
	Frequency Stability	±0.5ppm
	Operating Temperature	-4° F ~ 131° F
	Antenna Impedance	50 Ω
	Dimensions (HxWxD)	3.94 x 1.89 x 1.06 Inches
	Weight	4.76oz
	FCC ID	See website for full list
	Canada Industry ID	See website for full list

Your Local Dealer

EAGLE COMMUNICATIONS
34 Waterworks Way, Irvine, CA 92618

Toll Free 1 (800) 600-EAGLE
Local (949) 837-8788 (Orange County)
Fax (949) 837-2511
www.two-wayradio.com

Hytera reserves the right to change product designs or specifications at any time. If you have any questions regarding the accuracy of this information please contact your local sales representative or Hytera directly.

HYT, Hytera are registered trademarks of Hytera Co., Ltd. © 2014 Hytera Co., Ltd. All rights reserved.

Hytera Communications (Canada) Inc.

Address: 100 Leek Crescent, Unit 11
Richmond Hill, Ontario L4B 3E6
Tel: (905) 305-7545
http://www.hytera.ca

Hytera Communications America (West) Inc.

Address: 8 Whatney, Suite 200, Irvine, CA 92618
Tel: (949) 326-5740
http://www.hytera.us

Hytera
Respond & Achieve

EN20140228A